Revolix DUO - Why dual mode?

RevoLix DUO is the first universal laser in urology, which covers consistently lithotripsy, endourological soft tissue surgery and open surgery. This versatility is achieved by combining a pulsed and a 2micron continuous wave (cw) laser in one box.

2micron cw laser for soft tissue:

For surgical applications the 2micron cw laser is used. This laser was invented by LISA laser products specifically for incision, vaporisation and excision of soft tissue. The efficient vaporisation and cutting is striking. Vessels up to app. 1.5 mm diameter are closed while the damage zone is less than 1 mm. The necrotic zone of resected prostate tissue is less than 0.2 mm as shown in histologies.

Laser VapoResection of prostate (VRP) with the *RevoLix* laser is highly efficient, safe and economic for the treatment of BPH.

Contrary to other lasers the *Revolix* vaporesection procedure is performed with reusable front firing bare fibres. Tissue samples are available for subsequent histological examination.

Holmium pulse laser for lithotripsy:

Lithotripsy in the lower, medial and upper tract with rigid and flexible instruments is accomplished with the integrated Holmium laser. Laser pulses of maximal 7,000 watt peak power fragment any urinary stone irrespective of the chemical composition. Highly flexible laser fibres are most suitable for ureterorenoscopy of the lower calixes by flexible instruments.

Both laser units of the *RevoLix DUO* are available from the same fibre port. This feature allows using the same fibre for the vaporisation of tissue and the fragmentation of stones. There is no need to change the fibre or the instrument when changing between soft tissue and stone mode.

Technical Specifications Revolix Duo

Tissue laser system	continuous wave DPSS laser
Wavelength	2.0 micron
Power at tissue	adjustable 5 - 70 W
Emission mode	continuous wave, chopped 50 ms - 1000 ms
Stone laser system	pulsed Holmium-YAG laser
Wavelength	2.1 micron
Power at tissue	max. 20 W
Pulse energy	0.5 - 2.6 J
Repetition rate	5 - 15 Hz
Pulse peak power	6 kW
Beam delivery	wide range of flexible silica fibres
	same fibre port for both lasers
Aiming beam	635 nm, bright red, 1 mW, adjustable
Utilities	230 VAC, 1~, 50/60 Hz, 3.6 kVA, 500 μA leakage current
Cooling	integrated
Weight	165 kg
Dimensions	H 950 x W 420 x L 890 mm (height w/o display)

LASER CLASS 4/W
DPSS Laser; 2.0 µm, 7.0 W, CW
Holmium-VAG: 2.1 µm, 2.6.1 Max., 400 µs pulse
LASER (LASS 2.0)
Diode Laser: 6.35 nm, 1 mW, CW
VISIBLE AND INVISIBLE LASER RADIATION
AVOID ETE OR SIGN EXPOSURE
TO DIRECT OR SCATTERED RADIATION
LASER CLASS 4



Safety Standards: IEC 60601 CE approval pending

U.S. federal law restricts this device to sale by or on the order of a physician.

Specifications are subject to change without notice. Made in Germany 2008-09 V04

LISA laser products OHG Max - Planck - Str. 1 D - 37191 Katlenburg-Lindau Germany

fon: +49 (0)5556-9938-0 fax: +49 (0)5556-9938-10 e-mail: info@lisalaser.com web: www.lisalaser.com









new 2micron dual mode laser for soft tissue surgery and lithotripsy in Urology, ENT, Laparoscopy, Bronchoscopy, Gastroenterology, General Surgery

